## TECNO90



316081

FR47FE9

FREESTANDING SINGLE TANK 17L ELECTRIC FRYER WITH IN-TANK ROTATING HEATING ELEMENTS ON CLOSED CABINET - BASKETS, LIDS AND OIL DRAINING TANK INCLUDED



- Electric fryer 17 L on a closed cabinet (40 cm).
- Power: 16.5 kW.
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Deep drawn worktop with a seamlessly welded AISI 304 deep drawn cooking tank, featuring rounded corners.
- Rounded internal profile of the tank to facilitate cleaning, complying with hygiene standards.
- Large front basin and front zone for oil and foam expansion.
- Heating through AISI 304 stainless steel rotating armoured heating elements for easy cleaning of the tank and worktop.
- Operating thermostat ranging between 100°C and 190°C below oil smoke point.
- Bulb thermostats immersed in oil are more efficient in sensing the temperature inside the tank, promptly adjusting the oil to the desired temperature, minimising smoke points, and prolonging the oil life.
- A safety thermostat triggers in case of abnormal operation.
- Green light indicating voltage presence.
- Orange light indicating that the heating elements are heating up.
- Draining on the tank bottom.
- Tank with a filter for collecting oil inside the cabinet, baskets and lids included.
- Basket support fixed to the rear part of the worktop.
- Technical compartment for easy connection to the electrical network.
- AISI 304 stainless steel height-adjustable feet (133/195 mm)



46 cm

50 kg

0,53 m<sup>3</sup>

11550.0 W

16995.0 g/h

| 16,5 kW           | ELECTRIC POWER   | 16,5 kW  |
|-------------------|--|--|
| 50/60 Hz          | VOLTAGE  | 380-415 3N~ V  |
| 140÷190 °C        | TANK CAPACITY  | 17lt   |
| 30,7x34,2x25,7 cm | HEATING  | Heating elements in the tank   |
| 5 x 2,5 n° - mm²  | ELECTRIC CABLE TYPE  | H07 RN-F   |
| n° 1              | ELECTRICAL CONNECTION<br>HEIGHT (Y)  | -640 mm  |
| 133 mm            | FOOT ADJUSTMENT  | 133/195 mm   |
| 4                 | WIDTH  | 40 cm  |
| 90 cm             | HEIGHT   | 90 cm  |
|                   | 50/60 Hz  140÷190 °C  30,7x34,2x25,7 cm  5 x 2,5 n° - mm²  n° 1  133 mm  4 | 50/60 Hz  VOLTAGE  140÷190 °C  TANK CAPACITY  30,7x34,2x25,7 cm  HEATING  5 x 2,5 n° - mm²  ELECTRIC CABLE TYPE  n° 1  ELECTRICAL CONNECTION HEIGHT (Y)  133 mm  FOOT ADJUSTMENT  4  WIDTH |

PACKAGE DEPTH

STEAM RELEASE

LATENT HEAT RELEASE

**NET WEIGHT** 

VOLUME

## **ACCESSORIES**

PACKAGE WIDTH

PACKAGE HEIGHT

HARMONISED CODE

SENSIBLE HEAT RELEASE

**GROSS WEIGHT** 

| 310000 | REAR COVERING PANEL FOR CABINET (L=40CM)     |  |
|--------|--|--|
| 010000 | TILATI OOVERIINGT AINEET OF OADINET (L=400M) |  |

399573 PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

100 cm

115 cm

60 kg

84198180

1485.0 W

799507 EXTRA OIL-RECOVERY TANK FOR FRYERS (8+8L, 13L, 17L) 799508 EXTRA FRYER BASKET (17L) - DIM. CM (28.5X29.5X12H) 799509 2 EXTRA FRYER BASKETS (17L) - DIM. CM (14X29.5X12H)



## **INSTALLATION SCHEMES**

