## Series Delta / DELTA ES





## Technical description

Automatic machine with volumetric dosage.

- o Body in stainless steel
- o Moulded side panels polyurethane with stainless steel frame
- o Inbuilt volumetric pump with balanced by-pass
- o Coffee brewing with volumetric dosage (4 doses on each group, continuous brewing button)
- o Hot water delivery with time setting
- o Self-learning doses programming
- o Water mixer
- o Two steam wands in stainless steel with rubber grip and cool touch Teflon insert
- o Stainless steel hot water dispenser
- o Porta-filters with Magister OEM handles with cool touch grip
- o White LED back-lit six key touch panels with personalized Magister graphics
- LED indicators
- o LED lights on the working area
- o Electronic boiler temperature control adjustable through the touch pad
- Switching power unit stabilizing voltage fluctuations
- o Electronic pre-infusion which can be switched off through the panels
- Boiler level control and self-engaging heating element
- o 2 and 3 groups machines in three sizes: standard, "Tall-Cup" and High Group

## Optional accessories upon request:

- o Electronic cup warmer
- o Milk warmer/frother temperature-controlled steam wand "EPS"
- o Luxury version with mirror-polished side panels and chrome feet
- LED lighting on the side panels of the machine
- o OLED Display with 4 programming buttons. The display shows:
  - o machine name;
  - o temperature and water level in the boiler;
  - o coffee brewing timer on each group (chrono-function);
  - o alarms on maintenance;
  - o operational anomalies or failures;
- o Through the display buttons it is possible to set:
  - programmable on/off cycles;
  - o boiler temperature;
  - pre-infusion time;
  - o alarms on maintenance;
  - o chrono-function;

Model	DELTA ES	DELTA ES
Version	2 GROUPS	3 GROUPS
Dimensions mm.	830x535x500h	1070x535x500h
Dimensions mm.	830x535x580h	1070x535x580h
Boiler capacity	11 lt.	17 lt.
Power	4.500 Watt	5.400 Watt
Voltage	110-220/240V single phase, 230/380/415V threephase	220/240V single phase, 230/380/415V threephase
Weight	68 kg	88 kg
Colours		