

1N1FT4E



ELECTRIC GRIDDLE SMOOTH CHROMIUM PLATE ON CABINET

Griddle made of AISI 304 stainless steel, 20/10 mm thickness top. Cooking plate made in Fe510D steel with hard chromium surface treatment. COOKING-PRO SYSTEM. Delivered with: plate plug. Heating by two independent heating elements made in AISI 309 stainless steel placed under the plate, safety thermostat. Working temperature (min-max): 70-260°C. Pre-setting for remote control of power peaks. Integrated lower open compartment.



<i>Energy Control</i>	Pre-Setting for remote control of power peaks	<i>Plate</i>	Cr - smooth
<i>Power supply</i>	Electricity	<i>Product fitting up</i>	with integrated undercompartment
<i>Worktop thickness</i>	2 mm		

Functional features

- Smooth cooking plate made in special Fe510D steel with hard chromium surface treatment, thickness 15 mm.
- Plate sealed and slightly recessed into the worktop, obtained by a special mould hygienic design patented, with hard-chromium treatment, satin-finished
- Working temperature (min-max): 70-260°C.
- Cooking plate surface 715x635 mm.
- Specific output per useful surface dm² 226 W.
- n. 2 independent cooking areas power rated at 5.1 kW each
- COOKING PRO system ensures high performances, exceptional cooking uniformity, instant temperature recovery for continuous results and energy savings up to 20%. Electric elements are incorporated in an innovative multilayered material ensuring quick temperature rise, high efficiency in the heat transfer, temperature stability and energy efficiency.
- EASY-WASH: this is the program to clean the cooking plate bringing the surface temperature up to 75°C, in order to wash it reducing water and detergent.
- Commutable to 230V3 50/60 Hz
- Provision for remote peak power cut.
- Integrated lower open compartment.
- Pre-set appliance for installation freestanding on feet; with specific accessories on cantilever on beam, on multi-elements support.

Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- External panels in stainless steel, dashboard with side panels in AISI 304 stainless steel, Scotch Brite finish.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Fett drain outlet diameter 32 mm with removable heat-resistant food-grade plastic plug.
- Removable tray in the lower compartment, capacity 6 lt for cooking and washing liquids collection.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Radiused rear splashback on the worktop h = 4 cm, with built-in chimney for heat exhaust, removable enamelled cast iron guard.
- Access to all components through front compartment and control console.
- Height adjustable floor-mounted feet in AISI 304 stainless steel, non-scratch sole in insulating plastic material. Feet are supplied at a fixed height of 15 cm. Foot extension 5 cm (minimum height / maximum height: 87.5 / 92.5 cm).

Safety equipment and approvals

- Safety thermostat protecting the appliance and electric parts.
- Max temperature safety thermostat.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).



1N1FT4E



- IPX5 protection rating.

Optionals and Accessories

- Splash guards, cleaning plate scraper and blades; pipe for the water discharge during the cleaning of the plate.
- The lower compartment can be fitted with doors, wheels.

Technical Data

<i>Working voltage</i>	400V 3N~ / 230V 3~ / 50÷60 Hz	<i>Electric Power</i>	10,2 kW
<i>Dimensions</i>	80x92x90 cm	<i>Packing</i>	86x102x131 cm

ELECTRIC GRIDDLE SMOOTH CHROMIUM PLATE ON CABINET
Icon9000 prof.900 - 2 mm

