

### **OPERATING PRINCIPLE:**

The bacteria is sterilised by ultraviolet rays.

### L'HYGIENE :

Sloped top and bottom preventing any retention of water or dust. It is impossible to lay objects on the cabinet.

Removable stainless steel rack: it is dishwasher proof and easy cleaning of inside of cabinet.

### SAFETY:

The cabinet is fitted with a device to cut out the light when the door is opened: users are not exposed to UV rays. The stop holds the knives of cutter blades, thereby limiting any risks of them falling out and therefore injury.



Ref: 806 424

#### THE RANGE ALSO INCLUDES:

- 20-knife cabinet with grid ref. 806 421
- 10-knife cabinet with magnetic bar ref. 806 422

All the cabinets are also available with lock and kev.

# STERILIZING CABINETS

NEW: TIMER AT THE BOTTOM



Ref: 806 423

#### **EFFICIENCY**:

Thanks to the rack, no part of the knife's blade is in contact with a surface likely to obstruct the efficiency of the rays.

The stop is also provided to hold nonmagnetic utensils.

The cabinet is deep enough to allow for cutting disks (up to 157 mm) to be sterilised.

## **EYE-CATCHING:**

The radiused vertical edges give the cabinet a modern edge blending in with the Tournus stainless steel range.



Ref: 806 421



Ref: 806 422



## STERILIZING CABINETS

#### **TECHNICAL SPECIFICATIONS**

25 avenue Jean Moulin BP 59 71700 TOURNUS - FRANCE

#### FRANCE

Tél: 03 85 27 42 42 Fax: 03 85 27 42 50

E-mail:

commercial@tournus.con


#### EXPORT:


Tél: + 33 (0)3 85 27 42 65 Fax: + 33 (0)3 85 27 42 60


E-mail : export@tournus.com


Site Web:

- Stainless steel construction
- Colourless, transparent Plexiglas door with radiused corners, stainless steel hinges and magnetic fastening.
- Sloped top and bottom, stop in lower part
- Device to switch off the U.V. tube when the doors are opened
- Protected electrical part: IP 24
- Timer adjustable from 0 to 2 hours, minimum recommended: 1h30 min
- 230 V electrical connection, power supply cord 1.2 m long









Nominal voltageFrequency230V 1N~50 Hz

- Input power : 15 W or 30 W depending

on model

Appliance classificationProtection indexIP 24

- Standards : NF EN 60335-1

Description	Overall I x w x h dim.(mm)	Without key Ref.	With key Ref.
20-knife 1-door cabinet with stainless steel grid	575 x 170 x 600	806 421	816 421
10-knife 1-door cabinet with magnetic bar	575 x 170 x 600	806 422	816 422
20-knife 1-door cabinet with stainless steel grid	575 x 170 x 600	806 423	816 423
40-knife 2-door cabinet with stainless steel grid	1030 x 170 x 600	806 424	816 424

RC Mâcon B 383 567 104 Code APE 295 E SAS Capital 16 355 625 €