

THE PRODUCT LINE



054



084



134



154

All the innovative technology is in the background, assisting you in preparing even the most complex dishes, safe in the knowledge that the cooking parameters are correct. For anyone who is not seeking hard-core electronics, but wants to cook and program using simple, manual commands, without, however, forgoing the precision of digital controls.

For anyone looking for an oven that is easy to operate, but hard-wearing; suitable for everyone, but advanced, with a traditional approach, yet packed with content, an appliance that is reassuring and efficient, then LAINOX has just what you need. The solution is called Aroma Sapiens.

Aroma Sapiens is the oven providing assisted cooking with electronically-controlled manual commands. It includes LAINOX automatic programs: 64 pre-loaded cooking procedures, with room for up to 99 cooking procedures which can be programmed and stored by the user, each one of which can have up to 9 cycles in automatic sequence.

It also allows you to start manual cooking directly or to select a program with the dedicated scroller from your favourites with the scroll & push function.

DIRECT STEAM MODEL - STANDARD CONFIGURATION

Models	Power	EN chamber capacity (mm)	Pitch (mm)	Electrical power (kW)	Nominal gas thermal power (kW/kcal)	Absorption (A)	External dimensions (W x D x H mm)	Voltage power supply * (V)
ARES054B		5 x (600x400)	90	11,6	-/-	18	852 x 797 x 775	3N AC 400V - 50 Hz
ARGS054B		5 x (600x400)	90	0,7	13/11.180	3	852 x 797 x 775	AC 230V - 50 Hz
ARES084B		8 x (600x400)	90	18,7	-/-	29	852 x 797 x 1055	3N AC 400V - 50 Hz
ARGS084B		8 x (600x400)	90	0,8	22/18.920	3,5	852 x 797 x 1055	AC 230V - 50 Hz
ARES134B		5 x (600x400) + 8 x (600x400)	90	30,2	-/-	47	852 x 845 x 1840	3N AC 400V - 50 Hz
ARGS134B		5 x (600x400) + 8 x (600x400)	90	1,4	35/30.100	6,1	852 x 860 x 1840	AC 230V - 50 Hz
AREN154B		15 x (600x400)	89	37,2	-/-	58	892 x 862 x 1812	3N AC 400V - 50 Hz
ARGN154B		15 x (600x400)	89	1,3	44/37.840	5,7	892 x 862 x 1812	AC 230V - 50 Hz

* special voltages and frequencies upon request



MODEL 134

Versatility in a single unit, with 2 separate controls and two cooking chambers, capacity 5 x (600x400) + 8 x (600x400)