

# ELEVATORE PIATTI NEUTRI

## DISHES DISTRIBUTOR NEUTRAL TROLLEY



• **CSL/1N dimensioni mm 510x480x980 h**

Carrello elevatore piatti neutro ad una colonna senza regolazione diametro Ø 16-21 cm. per 50/60 piatti.

*Dishes distributor neutral trolley, stainless steel AISI 304 structure completely welded with one column for dishes elevator.*

*Diam. 16-21 Cm Cap. 50/60 round dished for CSL/1N model.*

*Dim. mm 510x480x980h*

• **CSP/1N dimensioni mm 510x480x1060 h**

Carrello elevatore piatti neutro ad una colonna con regolazione diametro Ø 18-28 cm. per 50/60 piatti.

*Dishes distributor neutral trolley with adjustable cylinder, stainless steel AISI 304 structure completely welded with one column for dishes elevator.*

*Diam. 18-28 Cm Cap. 50/60 round dished for CSP/1N model.*

*Dim. mm 510x480x1060 h*

• **CSG/1N dimensioni mm 560x530x1060 h**

Carrello elevatore piatti neutro ad una colonna con regolazione diametro Ø 28-32 cm. per 50/60 piatti.

*Dishes distributor neutral trolley with adjustable cylinder, stainless steel AISI 304 structure completely welded with one column for dishes elevator.*

*Diam. 28-32 cm Cap. 50/60 round dished for CSG/1N model. Dim. mm 560x530x1060 h*

• **CSL/2N dimensioni mm 930x480x980 h**

Carrello elevatore piatti neutro a due colonne senza regolazione diametro Ø 16-21 cm. per 100/120 piatti.

*Dishes distributor neutral trolley, stainless steel AISI 304 structure completely welded with the two columns for dishes elevator.*

*Diam. 16-21 cm Cap. 110/120 round dished for CSL/2N model.*

*Dim. mm 930x480x980 h*

• **CSP/2N dimensioni mm 930x480x1060 h**

Carrello elevatore piatti neutro a due colonne con regolazione diametro Ø 18-28 cm. per 100/120 piatti.

*Dishes distributor neutral trolley with adjustable cylinder, stainless steel AISI 304 structure completely welded with two columns for dishes elevator.*

*Diam. 18-28 cm Cap. 110/120 round dished for CSP/2N model.*

*Dim. mm 930x480x1060 h.*

• **CSG/2N dimensioni mm 1030x530x1060 h**

Carrello elevatore piatti neutro a due colonne con regolazione diametro Ø 28-32 cm. per 100/120 piatti.

*Dishes distributor neutral trolley with adjustable cylinders, stainless steel AISI 304 structure completely welded with two columns for dishes elevator.*

*Diam. 18-28 Cm. Cap. 110/120 round dished for CSG/2N model.*

*Dim. mm 1030x530x1060 h.*

• **CSL/4N dimensioni mm 930x905x980 h**

Carrello elevatore piatti neutro a quattro colonne senza regolazione diametro Ø 16-21 cm. per 200/240 piatti.

*Dishes distributor neutral trolley, stainless steel AISI 304 structure completely welded with four columns for dishes elevator.*

*Diam. 16-21 Cm Cap. 200/240 round dished for CSL/4N model.*

*Dim. mm 930x905x980 h*

• **CSP/4N dimensioni mm 930x905x1060 h**

Carrello elevatore piatti neutro a quattro colonne con regolazione diametro Ø 18-28 cm. per 200/240 piatti.

*Dishes distributor neutral trolley with adjustable cylinder, stainless steel AISI 304 structure completely welded with four columns for dishes elevator.*

*Diam. 18-28 Cm Cap. 200/240 round dished for CSP/4N model.*

*Dim. mm 930x905x1060 h*

• **CSG/4N dimensioni mm 1030x1005x1060 h**

Carrello elevatore piatti neutro a quattro colonne con regolazione diametro Ø 28-32 cm. per 200/240 piatti.

*Dishes distributor neutral trolley with adjustable cylinders, stainless steel AISI 304 structure completely welded with four columns for dishes elevator.*

*Diam. 18-28 Cm Cap. 200/240 round dished for CSG/4N model. Dim. mm 1030x1005x1060 h*

# ELEVATORE PIATTI RISCALDATI

## HEATED DISHES DISTRIBUTOR TROLLEY



• **CSL/1C, dimensioni mm 600x480x980 h, 900 W**

Carrello elevatore piatti riscaldato ad una colonna senza regolazione diametro, riscaldamento ventilato, Ø 16-21 cm per 50/60 piatti.

*Dishes distributor heated trolley, stainless steel AISI 304 structure completely welded with one heated column for dishes elevator diam. 16-21 cm. Cap. 50/60 round dished for CSL/1C model. Dim. mm 600x480x980 h, power 900 W*

• **CSP/1C, dimensioni mm 600x480x1060 h, 900 W**

Carrello elevatore piatti riscaldato ad una colonna con regolazione diametro, riscaldamento ventilato, Ø 18-28 cm per 50/60 piatti.

*Dishes distributor heated trolley with adjustable cylinder, stainless steel AISI 304 structure completely welded with one heated column for dishes elevator diam. 18-32 cm. Cap. 50/60 round dished for CSP/1C model. Dim. mm 600x480x1060 h, power 900 W*

• **CSG/1C, dimensioni mm 650x530x1060 h, 900 W**

Carrello elevatore piatti riscaldato ad una colonna con regolazione diametro, riscaldamento ventilato, Ø 28-32 cm per 50/60 piatti Ø 28-32 cm.

*Dishes distributor heated trolley with adjustable cylinder, stainless steel AISI 304 structure completely welded with one heated column for dishes elevator diam. 28-32 Cm. Cap. 50/60 round dished for CSG/1C model. Dim. mm 650x530x1060 h, power 900 W*

• **CSL/1S, dimensioni mm 600x480x980 h, 900 W**

Carrello elevatore piatti riscaldato ad una colonna senza regolazione diametro, Ø 16-21 cm per 50/60 piatti. Versione statica con termostato meccanico +30°/+90°C.

*Dishes distributor heated trolley, stainless steel AISI 304 structure completely welded with one heated column for dishes elevator diam. 16-21 cm. Cap. 50/60 round dished for CSL/1C model. Dim. mm 600x480x980 h, power 900 W. Static version with mechanical thermostat + 30°/+ 90°C.*

• **CSP/1S, dimensioni mm 600x480x1060 h, 900 W**

Carrello elevatore piatti riscaldato ad una colonna con regolazione diametro, Ø 18-28 cm per 50/60 piatti. Versione statica con termostato meccanico +30°/+90°C.

*Dishes distributor heated trolley with adjustable cylinder, stainless steel AISI 304 structure completely welded with one heated column for dishes elevator diam. 18-32 cm. Cap. 50/60 round dished for CSP/1C model. Dim. mm 600x480x1060 h, power 900 W. Static version with mechanical thermostat + 30°/+ 90°C.*

• **CSG/1S, dimensioni mm 650x530x1060 h, 900 W**

Carrello elevatore piatti riscaldato ad una colonna con regolazione diametro, Ø 28-32 cm per 50/60 piatti Ø 28-32 cm. Versione statica con termostato meccanico +30°/+90°C.

*Dishes distributor heated trolley with adjustable cylinder, stainless steel AISI 304 structure completely welded with one heated column for dishes elevator diam. 28-32 Cm. Cap. 50/60 round dished for CSG/1C model. Dim. mm 650x530x1060 h, power 900 W. Static version with mechanical thermostat + 30°/+ 90°C.*

• **CSL/2C, dimensioni mm 1030x480x980 h, 900W**

Carrello elevatore piatti riscaldato a due colonne senza regolazione diametro, riscaldamento ventilato, Ø 16-21 cm per 100/120 piatti.

*Dishes distributor heated trolley, stainless steel AISI 304 structure completely welded with two heated columns for dishes elevator diam. 16-21 Cm . Cap. 110/120 round dished for CSL/2C model. Dim. mm 1030x480x980 h, power 900 W*

• **CSP/2C, dimensioni mm 1030x480x1060 h, 900W**

Carrello elevatore piatti riscaldato a due colonne con regolazione diametro, riscaldamento ventilato, Ø 18-28 cm per 100/120 piatti.

*Dishes distributor heated trolley with adjustable cylinders, stainless steel AISI 304 structure completely welded with two heated columns for dishes elevator diam. 18-28 Cm. Cap. 110/120 round dished for CSP/2C model. Dim. mm 1030x480x1060 h, power 900 W*

• **CSG/2C, dimensioni mm 1130x530x1060 h, 900W**

Carrello elevatore piatti riscaldato ad due colonne con regolazione diametro, riscaldamento ventilato, Ø 28-32 cm per 100/120 piatti.

*Dishes distributor heated trolley with adjustable cylinders, stainless steel AISI 304 structure completely welded with two heated columns for dishes elevator diam. 28-32 Cm. Cap. 110/120 round dished for CSG/2C model. Dim. mm 1130x530x1060 h, power 900 W*

• **CSL/2S, dimensioni mm 1030x480x980 h, 900W**

Carrello elevatore piatti riscaldato a due colonne senza regolazione diametro, Ø 16-21 cm per 100/120 piatti. Versione statica con termostato meccanico +30°/+90°C.

*Dishes distributor heated trolley, stainless steel AISI 304 structure completely welded with two heated columns for dishes elevator diam. 16-21 Cm . Cap. 110/120 round dished for CSL/2C model. Dim. mm 1030x480x980 h, power 900 W. Static version with mechanical thermostat + 30°/+ 90°C.*

• **CSP/2S, dimensioni mm 1030x480x1060 h, 900W**

Carrello elevatore piatti riscaldato a due colonne con regolazione diametro, Ø 18-28 cm per 100/120 piatti. Versione statica con termostato meccanico +30°/+90°C.

*Dishes distributor heated trolley with adjustable cylinders, stainless steel AISI 304 structure completely welded with two heated columns for dishes elevator diam. 18-28 Cm. Cap. 110/120 round dished for CSP/2C model. Dim. mm 1030x480x1060 h, power 900 W. Static version with mechanical thermostat + 30°/+ 90°C.*

• **CSG/2S, dimensioni mm 1130x530x1060 h, 900W**

Carrello elevatore piatti riscaldato ad due colonne con regolazione diametro, Ø 28-32 cm per 100/120 piatti. Versione statica con termostato meccanico +30°/+90°C.

*Dishes distributor heated trolley with adjustable cylinders, stainless steel AISI 304 structure completely welded with two heated columns for dishes elevator diam. 28-32 Cm. Cap. 110/120 round dished for CSG/2C model. Dim. mm 1130x530x1060 h, power 900 W. Static version with mechanical thermostat + 30°/+ 90°C.*

• **CSL/4C, dimensioni mm 1020x905x980 h, 2000W**

Carrello elevatore piatti riscaldato a quattro colonne senza regolazione diametro, riscaldamento ventilato, Ø 16-21 cm per 200/240 piatti.

*Dishes distributor heated trolley, stainless steel AISI 304 structure completely welded with two heated columns for dishes elevator diam. 16-21 Cm. Cap. 200/240 round dished for CSL/4C model. Dim. mm 1020x905x980 h, power 2000 W*

• **CSP/4C, dimensioni mm 1020x905x1060 h, 2000W**

Carrello elevatore piatti riscaldato a quattro colonne con regolazione diametro, riscaldamento ventilato, Ø 18-28 cm per 200/240 piatti.

*Dishes distributor heated trolley with adjustable cylinders, stainless steel AISI 304 structure completely welded with two heated columns for dishes elevator diam. 18-28 Cm. Cap. 200/240 round dished for CSP/4C model. Dim. mm 1020x905x1060 h, power 2000 W*

• **CSG/4C, dimensioni mm 1120x1005x1060 h, 2000W**

Carrello elevatore piatti riscaldato ad quattro colonne con regolazione diametro, riscaldamento ventilato, Ø 28-32 cm per 200/240 piatti.

*Dishes distributor heated trolley with adjustable cylinders, stainless steel AISI 304 structure completely welded with four heated columns for dishes elevator diam. 28-32 Cm. Cap. 200/240 round dished for CSG/4C model. Dim. mm 1120x1005x1060 h, power 2000 W*