



The Refrigeration Experts

Product specification



EP700HL: 600 Ltr Cabinet Dual Temperature

41-487

Dual temperature cabinet

About the product

With EcoPro G3 Cabinets you get the best of both worlds: high performance coupled with low energy consumption, from the Refrigeration Experts.

Available to finance with our award-winning [interest-free credit](#) and [leasing](#) options

Learn more about our [EcoPro G3 range](#)

Why choose this product

- This model offers refrigerator and freezer temperatures in the same cabinet – perfect for when space is at a premium
- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage. With air distribution optimised by CFD design technology, efficient operation is assured, even when shelves are fully loaded
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer – all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 – the gold standard in performance stainless steel – meaning the heaviest usage touchpoints on the product are covered
- Market leading usable capacity, now supplied with 4 shelves as standard making your money go further – holds more than a conventional fridge
- Operates in ambient temperatures of up to 43°C
- This is a dual refrigeration system and requires two power supplies. Data about each system can be found in the spec table "Temperature" and "Temperature 2"

Specification

Technical

Temperature	Refrigerator +1/+4°C
Temperature 2	Freezer -18/-21°C
Fuse rating (A) 2	10
Current (A) 2	2.8
Power (w) 2	475
Refrigerant mass (g) 2	65
Thermal heat rejection (W)	240
Electrical supply	230/50/1
Current (A)	1.6
Power (W)	240
Refrigerant mass (g)	65
Refrigerant	R290

Dimensions

Height (mm)	2080
Width (mm)	700
Depth (mm)	825
Gross volume (ltr)	270
Net volume	177.4
GN size	2/1
Gross weight (kg)	158
Net weight (kg)	148
Gross volume (ltr) 2	270

Build

Cabinet type	Dual temperature
Finish ext/int	S/S & Alu
Number of sections	1
Section configuration	Right hinge
System	Integral
Leg type	Braked castors

Energy

Climate Class	5
Energy grade	C
EEI	42.47
AEC (kWh)	382.48
GWP	3
Energy grade 2	D
EEI 2	53.73
AEC (kWh) 2	1261
Energy consumption (kWh/24hr)	1.0479
Energy consumption (kWh/24hr) 2	3.45

Footnotes

- Castors are not available if product is supplied less condensing unit
- 100mm clearance is required above the cabinet to allow for adequate airflow and service access
- Depth with door open is 1500mm
- This is a dual refrigeration system – data about each system can be found in the spec table above for example “Temperature” and “Temperature 2”
- Supplied without lock

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.