

WOK INDUCTION PYROCERAM COOKING RANGE



Electric range with pyroceram surface with AISI 304 stainless steel structure, 20/10 mm thickness top. Cooking surface in pyroceram, flush with worktop and sealed. Induction heating. Kettle recognition sensor and automatic check devices. Forced cooling of electronic components. By the electromagnetic induction, pots of suitable material are required.



<i>Power supply</i>	Electricity	<i>Product fitting up</i>	Counter Top
<i>Worktop thickness</i>	2 mm		

Functional features

- Cooking surface in pyroceram, flush with worktop and sealed.
- Induction wok diameter 30 cm rated at 5 kW.
- Potentiometer with continuous power regulation from 1 to 10 .
- Very low radiation of heat to the environment and greater comfort for the operator, as all the power and heat are supplied to the base of the pan.
- Electronic diagnostic system with signaling alarm code through light on the controle console.
- Indirect cooking (not with contact) in pans certified for use on induction appliances.
- Heating induced in the ferro-magnetic material of the bottom of the container, through a field created by an electromagnetic inductor.
- Easy to clean thanks to a smooth, hermetic glass ceramic surface.
- Pre-set appliance for installation on under compartment, support surface; with specific accessories on bridge solution and cantilever on beam.

Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Control panel made in AISI 304 stainless steel, thickness 12/10 mm, Scotch-Brite finish. Side paneling made in AISI 304 stainless steel, back panel in stainless steel.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Pyroceram glass, thickness 6 mm, diameter 30 cm.
- Fan for the cooling the compartment housing the components with removable and dishwasher safe suction filter.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Radiused rear splashback on the worktop h = 4 cm, with built-in chimney for heat exhaust, removable enamelled cast iron guard.
- Non-slip rubber feet h = 2 cm.
- Access to all components through front compartment or control console.

Safety equipment and approvals

- Over temperature device on the glass for cutting power in case of abnormal operation.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- IPX4 protection rating.

Optional

- Wok pan for induction appliances.

Technical Data

<i>Working voltage</i>	400V 3N ~ 50 ÷60 Hz	<i>Electric Power</i>	5 kW
<i>Dimensions</i>	40x72x25 cm	<i>Packing</i>	46x82x65 cm