



## Refrigeration

NEO Concept Snack refrigerated counters

### FREEZER COUNTER, CMSN-150

#### DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	<b>1.492,00</b>	<b>1.500,00</b>
Depth	mm	<b>600,00</b>	<b>600,00</b>
Height	mm	<b>850,00</b>	<b>850,00</b>
Weigth	Kg	<b>100,00</b>	<b>120,00</b>
Volumen	m3	<b>0,76</b>	<b>0,77</b>

#### ELECTRICITY

<u>Electric power</u>	KW	<b>0,64</b>
230V - I+N		<b>2x1,5+T - 4 A</b>
230V - III		
400V - III+N		

#### WATER

Not used

#### GAS

Not used

#### SNACK SERIES FREEZER COUNTER, CMSN-150

Stainless steel exterior, except rear panel.  
Stainless steel interior, with rounded corners at the bottom.  
Stainless steel adjustable legs, . Rear guard of 10 cm.  
Internal shelves of plastic-coated steel, adjustable in height.  
Rotating door-type grid panel.  
Operating temperature -18°C, -22°C at room temperature of 38°C.  
Removable, ventilated airtight compressor.  
R-404 coolant.  
50-mm thick injected polyurethane insulation. Density 40 kg.  
No CFC.  
Copper tube evaporator with aluminium fins. Forced draught.  
Heating element in the door frame.  
Automatic evaporation of water during defrosting.  
Illuminated general switch.  
Electronic temperature and defrosting control and display.  
Doors with automatic locking device and fixed opening.  
Worktop with curved front.  
Operating voltage 220/240 V - I - 50/60 Hz.  
N. of doors: 2.  
Capacity (litres): 255.  
Refrigeration power: 348 W.  
Dimensions: 1.492 x 600 x 850 mm.  
Equipment: 1 grid per door.

#### STEAM

Not used

#### AIR

Not used

#### REFRIGERATION

R-404 A

#### Certificate EQNET- CE

SGS-2103-0906-1

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	214	5	310		Prever Interruptor diferencial

