



Refrigeration

NEO Concept Pizza and salad refrigerated counters

SALAD REFRIGERATED TABLE, CMEP-135

<u>DIMENSIONS</u>		<u>Article</u>	<u>Packed</u>	SALAD REFRIGERATED TABLE, CMEP-135 Stainless steel exterior, except rear panel.
Length	mm	1.342,00	1.540,00	Stainless steel interior, with rounded corners at the bottom.
Depth	mm	700,00	760,00	Stainless steel adjustable legs, .
Height	mm	850,00	940,00	Equipped with 2 pairs of 1/1 GN guides and 1 grid per door. Rotating door-type grid panel.
Weigth	Kg	84,00	91,00	Working temperature: -2 °C, +8 °C at room temperature of 38°C.
Volumen	m3	0,80	1,10	Removable, ventilated airtight compressor.
ELECTRICITY Electric power		KW	0,37	R-134 A coolant. 50-mm thick injected polyurethane insulation. Density 40 kg. No CFC. Copper evaporator with aluminium fins.
230V -1+N 230V - III 400V - III+N		2:	x1,5+T - 2 A	Forced draught. Automatic evaporation of water during defrosting. Illuminated general switch. Electronic temperature and defrosting control and display.
<u>WATER</u> Not used				Doors with automatic locking device and fixed opening. Worktop with curved front. Housings on tabletop for 1/1 GN containers, (containers no included).

GAS

Not used

Operating voltage 220/240 V – I – 50/60 Hz. N. of doors: 2.

Stainless steel cover (with fixed opening position).

Capacity for 3 containers 1/1 GN (Depth: 150 - 100 - 150)

Capacity (litres): 290. Refrigeration power: 250 W... Dimensions: 1.342 x 700 x 850 mm.

Optional gastronorm accessories.

STEAM Not used

<u>AIR</u> Not used

R-134 a REFRIGERATION

SGS-2103-0906-1 Certificate EQNET- CE

Connections points	X	Υ	Z	Diameter	Information
ELECTRICITY	214	5	310		Prever Interruptor diferencial

