salva





LABE LT-3+H - DIGITAL

The Labe LT-3+H DIGITAL oven is designed and ready to bake the product facing to the public. It is an electric convection oven with direct stem function which allows maximum flexibility and satisfy any coocking needs.

CHARACTERISTICS

- Stainless steel structure
 The oven is made of AISI 430 stainless steel, both the inside and the outside.
- Frontal door Provided with double glass, which allows viewing of the different phases of baking without opening it.
- Inner lighting

Thermal isolation

Thanks to the forced cooling system of the internal components.

- DIGITAL control panel
 - New design■

New cooking chamber geometry and newly shaped handlewith a modern design.

COMPOSITION AND TECHNICAL DETAILS

■LT-3+H - DIGITAL oven

3 trays of 60 x 40 cm.


Direction/sense: transversal.


Distance between sliders: 73 mm.

LT-3+H-DIGITAL data, monophasic

kW	V	А	Hz
3.7 I+T	220/230	16.1	50

GENERAL DIMENSIONS






■LT-3+H - DIGITAL weight: 45 kg.

X	Y	Z	
790 mm	750 mm	505* mm	

(*)If a support or a proofer is added, the oven would measure 1387 mm in height.

INSTALLATIONS IN DETAIL



A Baking steam outlet

B Water supply

The connection to the oven is made by flexible hose terminated in female 3/4" racord (supplied with the oven). The standpipe must have a constant pressure between 1-1.5 kg/cm².

C Electric power supply

The electrical connection must be performed by authorized professionals, according to applicable regulations of each country. Available in three phase and single phase.

Facilities location (mm)

www.salva.es

	Χ	Υ	Ζ
A Baking steam outlet	135	-	453*
B Water supply	300	-	60*
C Electric power supply	214	-	114*

(*)If a support or a proofer is added, the location of the installations would increase 882 mm in height, the rest would remain the same.

SALVA INDUSTRIAL S.A.
Polígono 107, GI-636, Km 6 E-20.100 Lezo (Guipuzkoa)

Technical sheet_LT-3+H - DIGITAL_(english)231017

e-mail España: salva@salva.es
e-mail Export: sales@salva.es

Tel. +34 943 449 300 / Fax. +34 943 449 329