

BLANCO INMOTION

Plate dispenser, heatable

- **Material CNS 18/10** with micro-polished surface,
- **Interior unit temperature** adjustable from +30°C to +110°C (2 SHVS 21-26: up to +130°C),
- **Powerful heating element** made of CNS 18/10,
- **With polycarbonate hooded cover** (with heated use of the units, operation should usually occur with the hooded cover to prevent unnecessary heat loss),
- **Synthetic guide rods** prevent porcelain from being worn,
- **Spring tension** can be adjusted to the weight of the respective plates,
- **CNS safety push handle** with side corner guard elements also serves to protect the switch elements,
- **Protected against splashed and sprayed water** (IPX 5),
- **Suitable for optimization systems**,
- Pursuant to **DIN 18665, Part 6**
- **Synthetic castors**, 4 steering castors, 2 of which have brakes, dia. 125 mm, corrosion-resistant pursuant to DIN 18867, Part 8,
- **Solid corner guards** made of plastic (polyamide) protect against damage,
- **VDE and GS certified, CE compliant**,
- **Operating panel** with on/off switch, pilot lamp, helix cord connection with dummy plug socket, temperature control on the short side below the push handle,
- **Mains voltage of SHV and SHVS:** 220-240 V, 50 Hz, **SHE:** 220-240 V, 50-60 Hz.



Model	1 SHE 21-26	1 SHE 26-31	2 SHE 21-26	2 SHE 26-31
	heatable	heatable	heatable	heatable
Dimensions LxWxH (in mm)	653 x 513 x 931 mm Operating height: 900 mm	653 x 513 x 931 mm Operating height: 900 mm	898 x 513 x 931 mm Operating height: 900 mm	1,018 x 513 x 931 mm Operating height: 900 mm
Interior dims (in mm)	dia. 210-260 mm	dia. 260-310 mm	dia. 210-260 mm	dia. 260-310 mm
Weight (in kg)	34.5 kg	35.0 kg	45.0 kg	49.5 kg
Wattage	0.9 kW	0.9 kW	1.8 kW	1.8 kW
Capacity	1 tube, approx. 60 plates total capacity	1 tube, approx. 60 plates total capacity	2 tubes, approx. 120 plates total capacity	2 tubes, approx. 120 plates total capacity
Stack height	w/o hooded cover: 620 mm w/ hooded cover: 670 mm (including hooded cover)	w/o hooded cover: 620 mm w/ hooded cover: 670 mm (including hooded cover)	w/o hooded cover: 620 mm w/ hooded cover: 670 mm (including hooded cover)	w/o hooded cover: 620 mm w/ hooded cover: 670 mm (including hooded cover)
Special features	Incl. polycarbonate hooded cover	Incl. polycarbonate hooded cover	Incl. polycarbonate hooded cover	Incl. polycarbonate hooded cover
Accessories/Options	Lid lock on the cover Decorative model For other castor designs, see Page 31	Lid lock on the cover Decorative model For other castor designs, see Page 31	Lid lock on the cover Decorative model For other castor designs, see Page 31	Lid lock on the cover Decorative model For other castor designs, see Page 31
Order No.	572 162	572 163	572 164	572 165