

TRUE FOOD SERVICE EQUIPMENT, INC.

2001 East Terra Lane • P.O. Box 970 • O'Fallon, Missouri 63366 (636)240-2400 • Fax (636)272-2408 • (800)325-6152 • Intl Fax# (001)636-272-7546 Parts Dept. (800)424-TRUE • Parts Dept. Fax# (636)272-9471 • www.truemfg.com

Project Name:	AIA #
Location:	
Item #: Qty:	SIS #
Model #:	

Model: GDM-23

Glass Door Merchandiser: Swing Door Refrigerator



GDM-23

- The world's #1 manufacturer of glass door merchandisers.
- Oversized, factory balanced, refrigeration system holds 33°F to 38°F (.5°C to 3.3°C).
- Exterior non-peel or chip white laminated vinyl; durable and permanent.
- Interior attractive, NSF approved, white aluminum interior liner with 300 series stainless steel floor.
- Self closing door. Positive seal, torsion type closure system.
- "Low-E", double pane thermal insulated glass door assembly with extruded aluminum frame. The latest in energy efficient technology.
- Patented integrated door light (IDL) system for brighter, shadow free illumination.
- Entire cabinet structure is foamedin-place using high density, CFC free, polyurethane insulation.

Bottom mounted units feature

- "No stoop" lower shelf to maximize product visibility.
- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning.

ROUGH-IN DATA

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

		Capacity (Cu. Ft.)		Cabinet Dimensions (inches) (mm)					NEMA	Cord Length (total ft.)	Crated Weight (lbs.)		
Model	Doors	(liters)	Shelves	L	D†	Н	HP	Voltage	Amps	Config.	(total m)	(kg)	
GDM-23	1	23	4	27	29 ⁷ /8	78 ⁵ /8	1/3	115/60/1	7.2	5-15P	9	315	1
		652		686	759	1998	1/3	230-240/50/1	3.0	A	2.74	143	

[†] Depth does not include 1¹/₈" (29 mm) for door handle.

▲ Plug type varies by country.



APPROVALS:

AVAILABLE AT:

GDM-23

Glass Door Merchandiser:

Swing Door Refrigerator



STANDARD FEATURES

DESIGN

 True's commitment to using the highest quality materials and oversized refrigeration systems provides the user with colder product temperatures, and lower utility costs in an attractive merchandiser that brilliantly displays packaged food and beverages.

REFRIGERATION SYSTEM

- Factory engineered self-contained, capillary tube system using environmentally friendly (CFC free) R134A refrigerant.
- Extra large evaporator coil balanced with higher horsepower compressor and large condenser; maintains cabinet temperatures of 33°F to 38°F (.5°C to 3.3°C).
- Sealed, cast iron, self-lubricating evaporator fan motor(s) and larger fan blades give True merchandisers a more efficient low velocity, high volume airflow design. This unique design ensures faster temperature pull down of warm product, colder holding temperatures and faster recovery in high use situations.
- Bottom mounted condensing unit positioned for easy maintenance. "No stoop" lower shelf maximizes visibility by raising merchandised product to higher level.

CABINET CONSTRUCTION

- Exterior non-peel or chip white laminated vinyl; durable and permanent.
- Interior attractive, NSF approved, white aluminum liner with 300 series stainless steel floor.
- Insulation entire cabinet structure is foamed-in-place using high density, CFC free, polyurethane insulation.
- Welded, heavy duty galvanized frame rail dipped in rust inhibiting enamel paint for corrosion protection inside and out.

- Frame rail fitted with leg levelers.
- Illuminated exterior sign panel. Variety of sign options available.

DOOF

- "Low-E", double pane thermal insulated glass door assembly with extruded aluminum frame. The latest in energy efficient technology.
- Door fitted with 12" (305 mm) extruded handle.
- Self closing door. Positive seal, torsion type closure system.
- Magnetic door gasket of one piece construction, removable without tools for ease of cleaning.

SHELVING

- Four (4) adjustable, heavy duty PVC coated wire shelves 22⁹/16"L x 23¹/4"D (574 mm x 591 mm).
 Four (4) chrome plated shelf clips included per shelf.
- Shelf support pilasters made of same material as cabinet interior; shelves are adjustable on 1/2" (13 mm) increments.

LIGHTING

- Safety shielded fluorescent interior lighting.
 Door utilizes full-length, patented, integrated doors light (IDL) system.
- Cabinet lighting utilizes electronic ballast and T-8 bulbs for brighter illumination, longer bulb life and increased energy efficiency.

MODEL FEATURES

- Evaporator is epoxy coated to eliminate the potential of corrosion.
- See our website www.truemfg.com for latest color and sign offerings.
- Convenient clean-out drain built in cabinet floor.
- Listed under NSF-7 for the storage and/or display of packaged or bottled product.

ELECTRICAL

 Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase
 15 amp dedicated outlet. Cord and plug set included.




OPTIONAL FEATURES / ACCESSORIES

Upcharge and lead times may apply.

- □ 230-240V / 50 Hz.
- ☐ Black exterior.
- $\hfill\square$ Rosewood exterior.
- ☐ Stainless steel exterior.
- ☐ Black aluminum interior liner with black shelving.
- ☐ Stainless steel interior liner.
- ☐ 6"(153 mm) standard legs.
- ☐ 6"(153 mm) seismic/flanged legs.
- \square 2¹/2"(64 mm) diameter castors.
- ☐ 4"(102 mm) diameter castors.
- ☐ Barrel locks (factory installed).
- ☐ Red wine thermostat.
- ☐ Chocolate thermostat.
- ☐ White wine thermostat.
- Novelty baskets.
- ☐ Wine racks.
- Additional shelves.
- ☐ TrueTrac4 gravity feed organizers.
- \square 1 $^{1}/_{4}$ " (32 mm) pricing strips.
- Remote cabinet and condensing unit. System comes standard with 404A expansion valve and requires R404A refrigerant.

PLAN VIEW



27"
(686 mm)

2913/16"
(758 mm)

13/32"
(28 mm)

2915/16"
(1391 mm)

2415/16"
(634 mm)

PLAN VIEW

WARRANTY

One year warranty on all parts and labor and an additional 4 year warranty on compressor. (U.S.A. only) METRIC DIMENSIONS ROUNDED UP TO THE NEAREST WHOLE MILLIMETER

SPECIFICATIONS SUBJECT TO CHANGE

KCL	Model	Elevation	Right	Plan	3D	
	GDM-23	TFAZ03E	TFAY03S	TFAZ03P	TFAZ033	

TRUE FOOD SERVICE EQUIPMENT