



## Speed, Performance, Value - The Right Balance

- Automatic memory accumulation
- Full range tare
- Check-weighing with low and high limits
- Check weighing LED bar graph
- Capacity tracker
- Large backlit LCD display
- Overload protection
- Grade 304 stainless steel pan
- RS-232 bi-directional interface
- Rechargeable battery up to 90 hours operation
- Easily accessible internal rechargeable battery
- Weighing
- Parts counting
- Percentage weighing
- Animal / dynamic weighing
- Check weighing
- Check counting



## Technical Specifications

Model	GFK 75	GFK 150	GFK 300	GFK 600	GFK 75H	GFK 150H
Maximum capacity	75kg	150kg	300kg	600kg	75kg	150kg
Readability	5g	10g	20g	50g	1g	2g
Repeatability (S.D.)	5g	10g	20g	50g	2g	4g
Linearity ( $\pm$ )	10g	20g	40g	100g	3g	6g
Units of measurement	Gram (g), Kilogram (kg)					Kilogram (kg)
Pan size	400x500mm			800x600mm	400x500mm	
Net weight	16kg			50kg	16kg	

## General Specifications

Typical stabilisation time	2-3 Sec
Operating temperature	-10°C - 40°C
Power supply	Internal rechargeable battery internal 230VAC or 120VAC 50/60Hz Transformer
Display	Backlit green display with 20mm digits and capacity tracker
Housing	ABS Plastic Indicator and Stainless Steel Pan
Overall dimensions (wxdxh)	400x620x860mm

## Key Accessories

- In-use Cover
- Adam Printer
- RS-232 to PC Cable
- Thermal Paper Roll for Adam Printer
- AdamDU - Data Collection Program
- RS-232 to USB Interface Cable (must be ordered with 30740102)
- ATP Thermal Printer
- Thermal Paper for ATP



**Adam Equipment - offices worldwide**

Pneutrol International Ltd, 5 Caulside Drive, Antrim, Northern Ireland, BT41 2DU  
[www.pneutrolspares.com](http://www.pneutrolspares.com), [sales@pneutrol.com](mailto:sales@pneutrol.com), Tel: +44 (0) 28 9448 1800