





ECOMAX G404

COMPACT GLASSWASHER

The fast and reliable glasswasher in compact design. Perfect for start-ups, small bars or restaurants.

FEATURES

- Electronic control with digital temperature NEW indication for easy operation
- Rotating wash and rinse arms for an even water distribution
- Indented nozzles prevent blocking
- Integrated counter for cycles and NEW water consumption, e.g. for control of water treatment system
- Deep drawn rack track for easy cleaning

- USB connection for easier service access NEW
- Include connection cable, supply and drain hose for immediate operation
- Thermostop function for guaranteed temperatures
- Self-cleaning programme for hygienic cleanliness also in the machine
- Switchable to thermolable temperature setting **NEW**
- Drain pump can be retrofitted









ECOMAX F504

DISHWASHER

With a high capacity of up to 60 racks per hour, this dishwasher is a reliable partner for club houses, bistros, and fast-food restaurants. The practical floor unit fits under every work counter.

FEATURES

- Electronic control with digital temperature NEW indication for easy operation
- Rotating wash and rinse arms for an even water distribution
- Indented nozzles prevent blocking
- Integrated counter for cycles and NEW water consumption, e.g. for control of water treatment system
- Deep drawn rack track for easy cleaning

- USB connection for easier service access **NEW**
- Include connection cable, supply and drain hose for immediate operation
- Thermostop function for guaranteed temperatures
- Self-cleaning programme for hygienic cleanliness also in the machine
- Tank strainer reduces soiling of the tank water **NEW**
- Switchable to thermolable temperature setting NEW
- Drain pump can be retrofitted





TECHNICAL SPECIFICATIONS




	ecomax [™] by (HOBART)		
MODELS	G404-10B	F504-30B	F504-32B
Cycle times*	60 / 120 sec.	60 / 150 sec.	60 / 150 sec.
Capacity cycles	60 /h	60 /h	60 /h
Tank capacity	10 I	25 I	25 I
Water consumption	2 l/rack	2.3 l/rack	2.3 l/rack
Wash pump	0.2 kW	0.35 kW	0.35 kW
Tank heating	1.8 kW	1.8 kW	1.8 kW
BOOSTER HEATING			
Standard	1.9 kW (230 V)	5.6 kW (400 V)	3.7 kW (1P)
Alternative	5.6 kW (400 V)	3.7 kW (230 V)	5.5 kW (3P)
TOTAL LOADING			
Standard	2.1 kW (230 V)	5.9 kW (400 V)	4.1 kW (1P)
Alternative	5.8 kW (400 V)	4.1 kW (230 V)	5.9 kW (3P)
Rated voltage	230/50/1 (400/50/3N)	400/50/3N (230/50/1)	230/60/1 (230/60/3)
Width	436 mm	576 mm	576 mm
Depth	534 mm	604 mm	604 mm
Height	700 mm	820 mm	820 mm
Loading height	308 mm	360 mm	360 mm
Rack size	390 x 390 mm	500 x 500 mm	500 x 500 mm


^{*} The machines are equipped with an automatic cycle-time control which ensures hygienic rinse temperatures even on a cold-water supply or with reduced heating performance.



Glasswasher model G404



Undercounter dishwasher model F504



HOBART GMBH

Robert-Bosch-Straße 17 | 77656 Offenburg | Germany Phone: +49(0)781.600-28 20 | Fax: +49(0)781.600-28 19

E-mail: info-export@hobart.de | Internet: www.hobart-export.com

HOBART INTERNATIONAL (S) PTE LTD

158 | Kallang Way | #06-03/05 | Singapore 349245

Phone: +65(0)6846 7117 | Fax: +65(0)6846 0991

E-mail: enquiry@hobart.com.sg | Internet: www.hobart.com.sg

Member of the ITW Food Equipment Group