



Catalogue

**CATERING** 

Chapter

**DISHWASHING** 

Model

CO-500 DD 230V 1N 50Hz

19057249 03/04/2019

### CO-500 DD DISHWASHER

- Front-loading dishwashers EVO Generation.
- Constructed in stainless steel.
- Whole body with double wall.
- Counterbalanced door with stainless steel hinges and double spring.
- Furniture which allows the machine to be positioned under 850 mm high work surfaces.
- Rounded tank to facilitate washing and drainage.
- Stainless steel armoured heating elements in the wash tank and rinse boiler.
- Useful internal height of 380 mm. Accepts GN 1/1 trays.
- 600 W wash pump
- Boiler with capacity of 7 litres.
- Magnetic safety stop switch in door opening.
- Safety thermostat
- Model with mechanical analogue control.
- 2 fixed wash cycles of 120" and 180".
- Theoretical maximum production of 30 baskets/hour.
- Tank with volume of 20 litres, with 2.8 kW heating element.
- 2.4 litre water consumption per cycle.
- Rinse with thermostop system. Standard factory setting disabled. Easy to enable.
- Tray-filter in the wash tank.
- IPX4 anti-humidity protection.
- Peristaltic detergent doser.

### Equipment included:

"One CT-10 base basket, 1 CP-16/18 basket for plates and two cutlery holders.

"

#### **DIMENSIONS**

Net volume



Gross volume

0,506 m3

## **ELECTRICITY TECHNICAL SPECIFICATIONS**

0,299

Electric power	3,400 kW
Heating power	2,80 kW
Voltage	230V - 1N
Amperage	14,7 A
Flectric frequency	50Hz

## WATER TECHNICAL SPECIFICATIONS

Pressure H2O: 200-400kPa(2-4bar)
Water max consumption 54,00 L/h

# CONNECTIONS TECHNICAL SPECIFICATIONS

230 V three-phase wiring  $3 \times 2,5 + T - 20A$  Single-phase 230V wiring  $2 \times 2,5 + T - 20 A$  Three-phase +N 40V wiring  $4 \times 1,5 + T - 16 A$  Hot softened water diameter 3/4" Drain 1 diameter 2"

## **OTHERS**

Noise level 65,00 dB















Catalogue CATERING

Chapter

**DISHWASHING** 

Model

CO-500 DD 230V 1N 50Hz

19057249 03/04/2019











